


VdTÜV-Kennblatt for welding consumables

		1 Manufacturer/Supplier MIGAL.CO GmbH Wattstraße 2 DEU 94405 Landau / Isar			2 No. of VdTÜV-Kennblatt: 11872.01 13.10.2017	
		3 Welding consumable*: Drahtelektrode				
4 Trade name*: ML 19.12.3 LSi						
7 Type*: EN ISO 14343-A - G 19 12 3 L Si						
11 Diameter range: 0,6 bis 1,6 mm						
12 Auxiliary materials: EN ISO 14175 - M 12						
13 The validity of this Kennblatt will be certified, respectively, in the latest edition of CD-ROM TÜV-eignungsgeprüfte Schweißzusätze						
15 Materials and postweld heat treatment						
Pos	Wb	Group / Material 1	Text	Group / Material 2	Remarks	
	U	Gruppe 8.1				
16 Material groups acc. to CR ISO 15608						
21 Root weldability: verified						
23 Wall thickness: maximal 30 mm						
24 Type of current and polarity: G+						
25 Welding position according to DIN EN ISO 6947:1997-05: PA, PB, PF						
26 Highest operating temperature in the short-term range as for parent metal, but not higher than: 400 °C						
27 Highest operating temperature in the long-term range max.: - - - °C						
28 Lowest operating temperature/as for parent metal, but not lower than: -196 °C						
29 Design stress value/as for parent metal: wie Grundwerkstoff						
30 For use in the long-term range: - - -						
31 Resistance to intergranular corrosion proven in accordance with: DIN 50914						
32 Remarks:						
33 The approval test was done on the basis of VdTÜV-Merkblatt 1153. Where nothing different is said under the heading -Remarks-, this welding consumable is suitable provided Annex I Point 4 of the Pressure Equipment Directive 97/23/EC is observed.						
34 Explanations						
		A tempered	S stress-relieved	W soft annealed	G+ direct current plus pole	
		L solution annealed and quenched	St stabilized		G- direct current minus pole	
		N normalized	U non-annealed		W alternating current	
			V hardened and tempered			
35 Compiled in accordance with the data of: TÜV Rheinland						
The duplication, circulation, copy and complete edition by photomechanical or similar techniques remain subject to the editor's approval even if only used in extracts. Editor: Verband der TÜV e. V. Distribution: TÜV-Media GmbH, Am Grauen Stein, 51105 Köln - Unternehmensgruppe TÜV Rheinland Group						

*) Statements of the manufacturer